# CRYSTAL NOUNTAIN PRODUCT BROCHURE





**MOGUL** POU Water Cooler

# **MOGUL** POU Water Cooler

The Mogul Point-of-Use water dispenser is available in Hot and Cold or Cook and Cold models. The Mogul's round and smooth shape fits into any living space. The contoured drip tray and a clean front complement each other's lines while achieving a usable platform to safely hold most cups. This commercial grade cooler will deliver years of trouble free optimum performance.





PP Faucet with self closing handle



Hermetically sealed reciprocating compressor



Hot water ON and OFF switch



Cup dispenser

## Point of Use system

The Point Of Use Kit uses a primary float with a secondary backup in conjunction with a 1/4" quick connect fitting with cover to protect the fitting and tubing. Easily adaptable, the double mechanical float system installs easily onto the coolers.





### **Performance and Specifications**

#### General

Air cooled, bottled type water cooler provided with a power supply cord for connection to the source of power supply

#### **Cooler Cabinet**

Blow moulded, high density polyethylene (HDPE) resistent to cracking, available in white and granite

#### Faucet Type

Concealed faucet for optimum hygiene Constructed of FDA approved nylon and silicon tubing Optional child lock safety function

#### **Cold Water Tank Specifications**

Stainless steel #304 or HDPE casing with 2.6L (0.7 gal) volume Cold water cooling capacity of 3.0L (0.8 gal)/hour based on 21°C (69.8°F) room temperature

#### **Cold Water Thermostat**

Preset at factory to dispense water at temperature from 4-10°C (39.2-50°F) Adjustable cold control located at the back of the cabinet

#### Hot Water Tank Specifications

Stainless steel #304 casing with 2.0L (0.5 gal) volume Hot water capacity of 4.5L (1.2 gal)/hour based on 21°C (69.8°F) room temperature

#### Hot Water Thermostats and Heater

Automatic thermostat control with temperature range of 74-92°C (165.2-197.6°F) Manual safety reset in case of automatic thermostat failure 450W external mica-heater band ON/OFF switch is located at the back of the cabinet Electronic Thermostat System (ETS) is available, which provides for a temperature control range of 88-92°C (190.4-197.6°F)

#### Compressor Type

Hermetically sealed reciprocating compressor 220 ~240VAC 50Hz

Refrigerant Type: R134a (CFC Free)

Refrigerant Charge: 25g (0.9 oz)

#### **Dimensions and Freight Data**

**Product Dimensions** 

325mm deep x 315mm wide x 985mm high

(12.8" deep x 12.4" wide x 38.8" high)

**Product Weight** Hot & Cold:13.2kg (29.0 lb) Cook & Cold:11.9kg (26.2 lb)

#### **Product Boxed Dimensions**

330mm deep x 320mm wide x 1000mm high (13.0" deep x 12.5" wide x 39.4" high)

Product Boxed Weight:

Hot & Cold:14.3kg (31.5 lb)

Cook & Cold:13.0kg (28.6 lb)

20FT Container Quantity: 252 Units 40FT Container Quantity: 518 Units



All performances are tested in a controlled environment, certified by a third party. To learn more about these standards, please speak to your Crystal Mountain representative.



#### Crystal Mountain Products Limited

European Sales Office Fence House, Fence Avenue Macclesfield, Cheshire United Kingdom SK10 1LT Tel: +44(0) 1625 439 111 Fax: +44 (0) 1625 502 527 E-mail: cmeurope@crystalcoolers.com

#### North American Sales Office

200 Carnegie Drive, Suite 234 St. Albert, AB, T8N 5A7 Canada Toll Free: 800 878 6422 Tel: 1 780 454 4545 E-mail: sales@crystalcoolers.com

#### **Crystal Mountain Products Inc.**

US Office / Warehouse 1665 Westbelt Drive Columbus, Oh 43228 Outbound Door #2 Tel: (614) 454 1618 Fax:(614) 409 9782 E-mail: sales@crystalcoolers.com

#### **Crystal Mountain International Limited**

#### Hong Kong Sales Office

Room 610, Winfield Commercial Building 6-8a Prat Avenue, Tsimshatsui Kowloon, Hong Kong Tel: (852) 2368 1989 Fax: (852) 3017 6727 E-mail: cmasia@crystalcoolers.com









#### Website: www.crystalcoolers.com

Crystal Mountain has a policy of continuous development and reserves the right to change specifications without notification.

