




Everest

Crystal Mountain is taking cooling the waters of the world to new heights with the introduction of the Everest. Its sleek two toned aesthetic will enhance any space. The sturdy and ergonomic faucet handles are 7" higher than traditional units, which enables effortless dispensing. The removable side panels facilitate access to all electrical components for easy maintenance and servicing. The innovative removable reservoir and faucet assembly make the cleaning and sanitizing process quick and simple. Crystal Mountain proves that anything is possible when there is a drive to overcome all obstacles.

Everest: Cook & Cold







Point of Use Kit



Filter storage compartment (Filter optional)

Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase
		220-240VAC 50Hz
Standard current		Cook & Cold: 0.6A
Power	Cold	80W
Consumption	Hot	450W
Cold	Compressor	Single phase motor
	Refrigerant	R134a
	Temp range	4-10°C (39.2-50°F)
	Temp control	thermostat (ON 12°C±1.5°C,OFF 2°C±1.5°C)
	Capacity	2.4L (0.6 gal)
Refrigerant charge		30g (1.1 oz)
Noise(sound power level)		44dB(A)
Product weight		Cook & Cold:11.6 kg (25.6 lb)
Product boxed weight		Cook & Cold:12.9 kg (28.4 lb)
Product dimensions		358.5(W) X 342(D) X 1058(H)mm
		14.1"(W) X 13.5 "(D) X41.7"(H)
Product boxed dimensions		330(W) X 330(D) X 1070(H)mm
		13.0"(W) X 13.0 "(D) X 42.1"(H)
Loading quantity		20' Container: 238Units
		40' Container: 504Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB



Cup dispenser version

Product weight	Cook & Cold:12.1 kg (26.7 lb)
Product boxed weight	Cook & Cold:13.4 kg (295 lb)
	358.5(W) X348(D) X1058(H)mm
Product dimensions	14.1"(W) X 13.7"(D) X 41.7"(H)

This Company has a policy of continuous development and reserves the right to change specifications without notification. For further clarifications, please contact us at sales@crystalcoolers.com.